TR 137 - Технические спецификации

Description

TR 137 — это шины компании BKT для всей техники, используемой для сбора урожая. Они обеспечивают высокую тягу в поле даже при большой нагрузке. Шины доступны в различных версиях: шины с брекером из арамидного волокна в версии «Aramid-belted» обеспечивают лучшее сопротивление проколам и защиту от всех характерных повреждений; шины в версии «HD» характеризуются невероятной стойкостью к порезам и разрывам, а также увеличенным сроком службы.

UM

US Standard

Construction

BIAS

Machinery

Сельское хозяйство: Комбайн

Version	STANDARD
Type	TL
Tyre Size	30.5L - 32
LI/SS	158 A8

Dimensions US Standard

Usa code	94004331
Ply Rating	12
Section Width (inch)	30.3
Overall Diameter (inch)	73.4
Static Loaded Radius (inch)	32.7
Rolling Circumference (inch)	217.3
Rim Rec	DH 27 B
Rim Alt	DW 27 B
ECE	E4-106R-002274
TRA Code	R1

Load capacity (lbs)

mph / psi	20
25	9350

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 12.10.2024 7:26

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..