

TR 144 - Технические спецификации



Description

Шины TR 144 подходят для небольших тракторов, используемых для обработки почвы. Шины TR 144 демонстрируют выдающиеся характеристики в любых условиях эксплуатации, а также гарантируют превосходную тягу при высокой нагрузке. Они также предлагаются в «специальной» версии, которая наилучшим образом предназначена для сложных условий эксплуатации.

UM

US Standard

Construction

 BIAS

Machinery

Сельское хозяйство: Мини-трактор

Version	SPECIAL
Type	TT
Tyre Size	8 - 18
LI/SS	90 A8

Dimensions US Standard

Usa code	94032013
Ply Rating	6
Section Width (inch)	7.7
Overall Diameter (inch)	32.9
Static Loaded Radius (inch)	15.4
Rolling Circumference (inch)	99.8
Rim Rec	W 6
Rim Alt	W 7 ; 5.50 F
ECE	E11-106R-003496
TRA Code	R1

Load capacity (lbs)

mph / psi	28
25	1325

Printed on 06.05.2024 17:28

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..