

## TR 171 - Технические спецификации



### Description

TR 171 — это шины с глубоким рисунком протектора, подходящие для тракторов, используемых при обработке почвы. Благодаря выдающимся свойствам самоочистки эти шины идеально подходят для эксплуатации на влажной и сырой почве. Шины TR 171 изготовлены из специальной резиновой смеси, что обеспечивает великолепную тягу и потрясающую прочность в условиях уборочных работ.

### UM

International Standard

### Construction

 BIAS

### Machinery

Сельское хозяйство: Трактор-тягач

Version	STANDARD
Type	TT
Tyre Size	16.9 - 30
LI/SS	137 A6

## Dimensions International Standard

Ply Rating	8
Section Width (mm)	430
Overall Diameter (mm)	1490
Static Loaded Radius (mm)	687
Rolling Circumference (mm)	4535
SRI (mm)	700
Rim Rec	W 15 L
Rim Alt	W 14 L
ECE	E11-106R-003588
TRA Code	R1W+

## Load capacity (Kg)

km/h / bar	1.70
30	2300

Printed on 03.03.2024 17:03

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..