

## TR 270 - Технические спецификации



### Description

TR 270 - это шины для тракторов, используемых для обработки почвы. Они специально разработаны для обеспечения максимальной производительности при эксплуатации на влажной и сырой почве. В таких почвенных условиях шины должны демонстрировать превосходное сцепление и улучшенные свойства самоочистки. Шины TR 270 полностью соответствуют всем этим требованиям.

### UM

US Standard

### Construction

 BIAS

### Machinery

Сельское хозяйство: Трактор-тягач

|           |           |
|-----------|-----------|
| Version   | STANDARD  |
| Type      | TT        |
| Tyre Size | 18.4 - 38 |
| LI/SS     | 149 A8    |

## Dimensions US Standard

|                              |                 |
|------------------------------|-----------------|
| Usa code                     | 94038947        |
| Ply Rating                   | 12              |
| Section Width (inch)         | 18.3            |
| Overall Diameter (inch)      | 70.2            |
| Static Loaded Radius (inch)  | 32.4            |
| Rolling Circumference (inch) | 210             |
| Rim Rec                      | W 16 A ; W 16 L |
| Rim Alt                      | W 15 L ; DD 16  |
| ECE                          | E11-106R-004511 |
| TRA Code                     | R2              |

## Load capacity (lbs)

|           |      |
|-----------|------|
| mph / psi | 32   |
| 25        | 7150 |

Printed on 27.04.2024 7:22

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..