

TR 273 - Технические спецификации



Description

TR 273 - это шины для пахотных тракторов, которые были специально разработаны для обеспечения максимальной производительности при эксплуатации на влажной и сырой почве. В таких почвенных условиях шины должны демонстрировать превосходное сцепление и улучшенные свойства самоочистения. Шины TR 273 полностью соответствуют всем этим требованиям.

UM

US Standard

Construction

 BIAS

Machinery

Сельское хозяйство: Трактор-тягач

Version	STANDARD
Type	TT
Tyre Size	23.1 - 34
LI/SS	157 A8

Dimensions US Standard

Usa code	94045907
Ply Rating	14
TMPH	1
Section Width (inch)	23.2
Overall Diameter (inch)	72.8
Static Loaded Radius (inch)	32.8
Rolling Circumference (inch)	221.8
Rim Rec	DW 20 A ; DW 20 B
ECE	E11-106R-003646
TRA Code	R2

Load capacity (lbs)

mph / psi	30
25	8820

Printed on 26.04.2024 10:35

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..