

TR 315 - Технические спецификации



Description

Шины TR 315 подходят для работ в саду, обработки почвы и муниципальных работ. Это идеальные шины для сельскохозяйственной техники, траншеекопателей и садовых комбайнов. Шины TR 315 имеют большую площадь пятна контакта, что обеспечивает превосходное сцепление, отличное самоочистение и выдающуюся устойчивость в любых условиях.

UM

US Standard

Construction

 BIAS

Machinery

Сельское хозяйство: Сельскохозяйственное оборудование •
Машина для сбора фруктов • Траншейный экскаватор

Version	STANDARD
Type	TL
Tyre Size	16 X 6.50 - 8

Dimensions US Standard

Usa code	94022274
Ply Rating	6
Section Width (inch)	6.1
Overall Diameter (inch)	16.1
Static Loaded Radius (inch)	7.2
Rolling Circumference (inch)	46.6
Rim Rec	5.375 I - 55 ; I - 70 ; I - 90
ECE	E4-106R-002175

Load capacity (lbs)

mph / psi	42
10	785

Printed on 08.05.2024 18:36

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..