

TR 318 - Технические спецификации



Description

Шины TR 318 предназначены для опрыскивателей и другой сельскохозяйственной техники. Расположенные под двумя разными углами грунтозацепы гарантируют отличную тягу и выдающийся комфорт в движении. Шины TR 318 также отличаются великолепными характеристиками самоочистения.

UM

US Standard

Construction

 BIAS

Machinery

Сельское хозяйство: Сельскохозяйственное оборудование •
Опрыскиватель

| | |
|-----------|----------------|
| Version | STANDARD |
| Type | TT |
| Tyre Size | 23 X 9.00 - 12 |
| LI/SS | 93 A3 |

Dimensions US Standard

| | |
|-------------------------|-----------------|
| Usa code | 94052110 |
| Ply Rating | 6 |
| Section Width (inch) | 8.7 |
| Overall Diameter (inch) | 23 |
| Rim Rec | 7.0 |
| ECE | E11-106R-004521 |

Load capacity (lbs)

| | |
|-----------|------|
| mph / psi | 43 |
| 10 | 1433 |

Printed on 23.04.2024 15:16

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..