TR 360 - Технические спецификации

Description

Шины TR 360 подходят для сельскохозяйственной техники. Они предназначены для перевозок в условиях бездорожья, а также для садово-огородных работ. Специальный рисунок протектора и конструкция каркаса обеспечивают долгий срок службы шин.

UM

International Standard

Construction

BIAS

Machinery

Сельское хозяйство: Сельскохозяйственное оборудование

Version	STANDARD
Type	TL
Tyre Size	18 X 7 - 8

Dimensions International Standard

Ply Rating	6
Section Width (mm)	180
Overall Diameter (mm)	460
Static Loaded Radius (mm)	202
Rolling Circumference (mm)	1334
Rim Rec	5.5
ECE	E4-106R-002184

Load capacity (Kg)

km/h / bar	3.10
15	450

Printed on 02.05.2024 9:59

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..