TR 390 - Технические спецификации

Description

TR 390 — это агропромышленные шины, предназначенные для перевозки сахарного тростника на прицепах и уплотнительной техники. TR 390 отличаются исключительной грузоподъемностью и высокой долговечностью. Версия «Dual Bead HD» особенно подходит для промышленных тракторов и прицепов, используемых для грузовых перевозок, а версия «Dual Bead HD special» — идеальный вариант для техники, работающей в условиях больших нагрузок.

UM

US Standard

Construction

BIAS

Machinery

Сельское хозяйство: Прицеп
Производство: уплотнительная техника

Version	DUAL BEAD HD
Type	TL
Tyre Size	28L - 26
LI/SS	168 A8

Dimensions US Standard

Usa code	94047048
Ply Rating	20
Section Width (inch)	28.1
Overall Diameter (inch)	61.4
Static Loaded Radius (inch)	27.2
Rolling Circumference (inch)	178.9
Rim Rec	DW 25 B
Rim Alt	DW 23 B
ECE	E11-106R-004609
TRA Code	R3

Load capacity (lbs)

mph / psi	42
25	12350

Printed on 29.04.2024 10:37

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..