

TR 391 - Технические спецификации



Description

TR 391 — это агропромышленные шины, подходящие для прицепов для сахарного тростника и катков, которые используются для перевозки и уплотнительных работ. TR 391 отличаются исключительной грузоподъемностью и долгим сроком службы.

UM

US Standard

Construction

 BIAS

Machinery

Сельское хозяйство: Прицеп

Производство: уплотнительная техника

| | |
|-----------|-----------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | 14.9 - 24 |
| LI/SS | 124 A8 |

Dimensions US Standard

| | |
|------------------------------|-------------------------|
| Usa code | 94005277 |
| Ply Rating | 8 |
| Section Width (inch) | 15.9 |
| Overall Diameter (inch) | 50 |
| Static Loaded Radius (inch) | 22.6 |
| Rolling Circumference (inch) | 149.8 |
| Rim Rec | DW 13 |
| Rim Alt | DW 11 ; DW 12 ; DW 13 L |
| ECE | E11-106R-003365 |
| TRA Code | R3 |

Load capacity (lbs)

| | |
|-----------|------|
| mph / psi | 26 |
| 25 | 3520 |

Printed on 22.02.2024 21:11

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..