

TR 393 (B) - Загрузить лист технических данных



Description

Шина TR 393 (B) разработана специально для сеялок и другого сельскохозяйственного оборудования, эксплуатируемого как на дороге, так и на бездорожье. Высокая проходимость, отличные характеристики самоочистки и долгий срок службы гарантированы особым рисунком протектора. Благодаря большому пятну контакта шина TR 393 (B) обеспечивает превосходную тягу и сводит к минимуму уплотнение почвы.

UM

International Standard

Construction

 BIAS

Machinery

Сельское хозяйство: Пресс-подборщик •
Сельскохозяйственное оборудование • Разбрасыватель

SIZE	Version	TRA Code	LI/SS	PR	RIM REC	RIM ALT	SW	OD	Type	ECE
31 X 13.50 - 15	STUBBLE RESISTANT	R3	124 B	12	10 LB		350	777	TL	E11-106R-008131

Printed on 04.03.2024 13:23

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..