

TR 459 - Технические спецификации



Description

Шины TR 459 специально разработаны для тракторов и экскаваторов-погрузчиков, используемых для землеройных, погрузочных, а также коммунальных и ремонтных работ. Они отличаются высокой стабильностью и предлагаются в двух версиях. Специальная версия гарантирует увеличенный срок службы шины.

UM

International Standard

Construction

 BIAS

Machinery

Сельское хозяйство: Экскаватор-погрузчик • Трактор-тягач
Производство: экскаватор-погрузчик

Version	INDUSTRIAL
Type	TL
Tyre Size	18.4 - 24
LI/SS	155 A8

Dimensions International Standard

Ply Rating	12
Section Width (mm)	472
Overall Diameter (mm)	1375
Static Loaded Radius (mm)	610
Rolling Circumference (mm)	4114
Rim Rec	DW 16 L
Rim Alt	DW 15 L
ECE	E11-106R-005217
TRA Code	R4

Load capacity (Kg)

km/h / bar	2.50
40	3875

Printed on 24.04.2024 8:45

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..