

## TR 459 - Технические спецификации



### Description

Шины TR 459 специально разработаны для тракторов и экскаваторов-погрузчиков, используемых для землеройных, погрузочных, а также коммунальных и ремонтных работ. Они отличаются высокой стабильностью и предлагаются в двух версиях. Специальная версия гарантирует увеличенный срок службы шины.

### UM

US Standard

### Construction

 BIAS

### Machinery

Сельское хозяйство: Экскаватор-погрузчик • Трактор-тягач  
Производство: экскаватор-погрузчик

|           |            |
|-----------|------------|
| Version   | INDUSTRIAL |
| Type      | TL         |
| Tyre Size | 19.5L - 24 |
| LI/SS     | 147 A8     |

## Dimensions US Standard

|                              |                 |
|------------------------------|-----------------|
| Usa code                     | 94016662        |
| Ply Rating                   | 10              |
| Section Width (inch)         | 19.3            |
| Overall Diameter (inch)      | 52.5            |
| Static Loaded Radius (inch)  | 23              |
| Rolling Circumference (inch) | 158.7           |
| Rim Rec                      | DW 16 L         |
| ECE                          | E11-106R-005334 |
| TRA Code                     | R4              |

## Load capacity (lbs)

|           |      |
|-----------|------|
| mph / psi | 28   |
| 25        | 6800 |

Printed on 24.04.2024 6:58

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..