

## TRAC FARM PLUS - Технические спецификации



### Description

TRAC FARM PLUS — это шины для задних колес тракторов, специально предназначенные для обработки почвы и грузоперевозок. Глубокий рисунок протектора с грунтозацепами, расположенными под двумя углами, гарантирует превосходную тягу и комфорт при движении по дороге. Специальный рисунок протектора обеспечивает увеличенное пятно контакта для лучшей устойчивости и хорошего самоочистения. Шины TRAC FARM PLUS отличаются долгим сроком службы.

### UM

US Standard

### Construction

BIAS

### Machinery

Сельское хозяйство: Трактор-тягач

Version	STANDARD
Type	TT
Tyre Size	13.6 - 28
LI/SS	124 A8

## Dimensions US Standard

Usa code	94045686
Ply Rating	12
Section Width (inch)	14.4
Overall Diameter (inch)	53
Static Loaded Radius (inch)	24.4
Rolling Circumference (inch)	160.9
Rim Rec	W 12
Rim Alt	W 11
ECE	E11-106R-004527
TRA Code	R1

## Load capacity (lbs)

mph / psi	34
25	3530

Printed on 27.04.2024 4:33

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..