

## TRAC FARM - Технические спецификации



### Description

TRAC FARM — это шины для тракторов, используемых для обработки почвы и грузоперевозок, специально рассчитанные на эксплуатацию при больших нагрузках. Глубокий рисунок протектора и устойчивая к порезам и разрывам специальная резиновая смесь позволяют использовать шины в самых трудных условиях, обеспечивая при этом лучший возврат инвестиций за время всего жизненного цикла продукта. Шины TRAC FARM обладают большим количеством грунтозацепов, обеспечивая превосходную тягу и самоочищение.

### UM

US Standard

### Construction

 BIAS

### Machinery

Сельское хозяйство: Трактор-тягач

Version	HD
Type	TT
Tyre Size	18.4 - 30
LI/SS	147 A8

## Dimensions US Standard

Usa code	94049905
Ply Rating	14
Section Width (inch)	18.5
Overall Diameter (inch)	61.6
Static Loaded Radius (inch)	28.2
Rolling Circumference (inch)	179.4
Rim Rec	W 16 L
Rim Alt	W 15 L
ECE	E11-106R-004525
TRA Code	R1

## Load capacity (lbs)

mph / psi	38
25	6780

Printed on 25.04.2024 21:31

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..