

TRAC GRADER + - Технические спецификации



Description

TRAC GRADER + (G-2) - это диагональные шины для грейдеров. Это отличный выбор для тех клиентов, кто ищет недорогие решения. Прочный каркас обеспечит долговечность. А самоочищающийся протектор имеет такой коэффициент пустотности, который обеспечивает лучшую тягу в любых условиях эксплуатации. Шины в версии «Special» выполнены с использованием специальной резиновой смеси протектора, стойкой к порезам и разрывам.

UM

US Standard

Construction

❧ BIAS

Machinery

Производство: Грейдер

Version	SPECIAL
Type	TL
Tyre Size	13.00 - 24

Dimensions US Standard

Usa code	94014668
Ply Rating	12
Overall Width (inch)	13.4
Overall Diameter (inch)	50.4
Static Loaded Radius (inch)	23.6
Rolling Circumference (inch)	155.2
Rim Rec	8.00 TG SDC
Rim Alt	9.00/1.5 (DC) ; 10.00/VA SDC
TRA Code	G2
Tread Depth	32

Load capacity (lbs)

mph / psi	44
25	6000

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 01.06.2025 21:15

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..