

## TRAC GRADER + - Технические спецификации



### Description

TRAC GRADER + (G-2) - это диагональные шины для грейдеров. Это отличный выбор для тех клиентов, кто ищет недорогие решения. Прочный каркас обеспечит долговечность. А самоочищающийся протектор имеет такой коэффициент пустотности, который обеспечивает лучшую тягу в любых условиях эксплуатации. Шины в версии «Special» выполнены с использованием специальной резиновой смеси протектора, стойкой к порезам и разрывам.

### UM

International Standard

### Construction

✦ BIAS

### Machinery

Производство: Грейдер

Version	STANDARD
Type	TL
Tyre Size	14.00 - 24

## Dimensions International Standard

Ply Rating	16
Overall Width (mm)	364
Overall Diameter (mm)	1348
Static Loaded Radius (mm)	598
Rolling Circumference (mm)	3990
Rim Rec	8.00 TG SDC
Rim Alt	9.00/1.5 (DC) ; 10.00/VA SDC
TRA Code	G2

## Load capacity (Kg)

km/h / bar	3.50
40	3650

Printed on 20.04.2024 10:17

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..