

## TRAC MASTER - Технические спецификации



### Description

TRAC MASTER — это шины для машин, используемых для обработки почвы и садово-огородных работ. Они подходят для небольших тракторов и другой сельскохозяйственной техники. Рисунок протектора гарантирует превосходную защиту в полевых условиях наряду с отличной тягой и оптимальными свойствами самоочистки.

### UM

International Standard

### Construction

 BIAS

### Machinery

Сельское хозяйство: Сельскохозяйственное оборудование •  
Мини-трактор

|           |                 |
|-----------|-----------------|
| Version   | STANDARD        |
| Type      | TL              |
| Tyre Size | 31 X 15.50 - 15 |

## Dimensions International Standard

|                            |                |
|----------------------------|----------------|
| Ply Rating                 | 6              |
| Section Width (mm)         | 405            |
| Overall Diameter (mm)      | 792            |
| Static Loaded Radius (mm)  | 370            |
| Rolling Circumference (mm) | 2372           |
| Rim Rec                    | 13 LB          |
| ECE                        | E4-106R-002209 |

## Load capacity (Kg)

| km/h / bar | 2.10 |
|------------|------|
| 50         | 975  |

Printed on 27.04.2024 4:35

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..