

TRAC SUPER - Технические спецификации



Description

TRAC SUPER — это первые радиальные шины, которые компания BKT предлагает для сегмента муниципальной техники. Конструкция шин со стальным бреккером гарантирует превосходное плавное перемещение и отличную тягу. Поэтому эти шины особенно подходят для эксплуатации на просторных газонных поверхностях, таких как парки и обочины.

UM

International Standard

Construction

 RADIAL

Machinery

Сельское хозяйство: Мини-трактор

Version	STANDARD
Type	TL
Tyre Size	500/50 R 17
LI/SS	147 D

Dimensions International Standard

Section Width (mm)	490
Overall Diameter (mm)	940
SRI (mm)	450
Rim Rec	16.00
ECE	E11-106R-007767

Load capacity (Kg)

km/h / bar	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0	4.5
65	1200	1450	1665	1940	2185	2400	2645	2895	3075
40	1635	1970	2260	2640	2975	3265	3600	3935	4185
30	1815	2185	2510	2930	3300	3625	3995	4370	4645
10	2160	2605	2990	3490	3930	4320	4765	5205	5535

Printed on 26.04.2024 21:13

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..