

VIJETA - Технические спецификации



Description

VIJETA - это сельскохозяйственные шины для эксплуатации как на дорогах, так и в условиях бездорожья. 5-реберный рисунок протектора оптимизирует распределение нагрузки. Кроме того, износостойкая резиновая смесь и прочный каркас обеспечивают длительный срок службы шины.

UM

International Standard

Construction

 BIAS

Machinery

Сельское хозяйство: Прицеп

Version	STANDARD
Type	TT
Tyre Size	7.00 - 19

Dimensions International Standard

Ply Rating	10
Section Width (mm)	195
Overall Diameter (mm)	852
Rim Rec	5.00
ECE	E11-106R-004106

Load capacity (Kg)

km/h / bar	5.15
15	1360

Printed on 25.04.2024 19:28

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..