

XL GRIP (ADT) - Технические спецификации



Description

XL GRIP (ADT) — это диагональные шины для шарнирно-сочлененных самосвалов. Они минимизируют повреждения и царапины при работе техники в тяжелых условиях, когда требуется хорошее сцепление с поверхностью. Помимо этих преимуществ, шины отличаются долгим сроком службы.

UM

International Standard

Construction

 BIAS

Machinery

Производство: Шарнирно-сочлененный самосвал

| | |
|-----------|-----------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | 29.5 - 25 |

Dimensions International Standard

| | |
|----------------------------|-----------|
| Ply Rating | 32 |
| Overall Width (mm) | 760 |
| Overall Diameter (mm) | 1860 |
| Static Loaded Radius (mm) | 849 |
| Rolling Circumference (mm) | 5544 |
| Rim Rec | 25.00/3.5 |
| TRA Code | E3 |

Load capacity (Kg)

| | |
|------------|-------|
| km/h / bar | 3.75 |
| 50 | 12500 |

Printed on 06.05.2024 17:48

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..