

XL GRIP (E3) - Технические спецификации



Description

XL GRIP (E-3) - это диагональные шины для самосвалов с жесткой рамой. Они минимизируют повреждения и царапины при работе техники в тяжелых условиях, когда требуется хорошее сцепление с поверхностью. Помимо этих преимуществ, шины отличаются долгим сроком службы.

UM

US Standard

Construction

✚ BIAS

Machinery

Производство: Самосвал с жесткой рамой

Version	STANDARD
Type	TL
Tyre Size	16.00 - 25

Dimensions US Standard

Usa code	94015689
Ply Rating	28
Overall Width (inch)	18.3
Overall Diameter (inch)	58.5
Static Loaded Radius (inch)	26.9
Rolling Circumference (inch)	173
Rim Rec	11.25/2.0
Rim Alt	13.00/2.0
TRA Code	E3/L3
Tread Depth	37

Load capacity (lbs)

mph / psi	83	109
30	14800	-
5	-	25400

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 11.05.2025 22:18

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..