

XL GRIP IND3 (ECH) - Технические спецификации



Description

XL GRIP (IND-3) — это диагональные шины для укладчиков и погрузчиков пустых контейнеров, используемых для складских работ. Прочный каркас этой шины обеспечивает превосходную надежность, а также прекрасную устойчивость при подъеме грузов.

UM

International Standard

Construction

 BIAS

Machinery

Производство: Погрузчик пустых контейнеров

Version	INDUSTRIAL
Type	TL
Tyre Size	16.00 - 25

Dimensions International Standard

Ply Rating	28
Overall Width (mm)	465
Overall Diameter (mm)	1485
Static Loaded Radius (mm)	682
Rolling Circumference (mm)	4395
Rim Rec	11.25/2.0
Rim Alt	13.00/2.0
TRA Code	IND3

Load capacity (Kg)

km/h / bar	9.00
10	15525

Printed on 20.04.2024 17:37

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..