

XL GRIP (L3) - Технические спецификации



Description

XL GRIP (E-3/L-3) - это широкие диагональные шины для погрузчиков, разработанные для снижения повреждений и порезов при работе в тяжелых условиях. Они обеспечивают исключительное сцепление с дорогой и отличаются долгим сроком службы.

UM

International Standard

Construction

✚ BIAS

Machinery

Производство: Погрузчик

Производство: Бульдозер • Погрузчик

Version	STANDARD
Type	TL
Tyre Size	20.5 - 25

Dimensions International Standard

Ply Rating	12
Overall Width (mm)	530
Overall Diameter (mm)	1485
Static Loaded Radius (mm)	682
Rolling Circumference (mm)	4395
Rim Rec	17.00/2.0
TRA Code	E3/L3

Load capacity (Kg)

km/h / bar	2.00	2.50
50	4500	-
10	-	6700

Printed on 18.04.2024 18:55

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..