

XL GRIP PLUS - Технические спецификации



Description

Шина XL GRIP PLUS (L-4) разработана специально для эксплуатации на погрузчиках. Благодаря высокому протектору она обладает превосходной стойкостью к порезам и проколам, а также отличается увеличенным сроком службы. Шина XL GRIP PLUS рекомендована для эксплуатации в суровых условиях.

UM

US Standard

Construction

 BIAS

Machinery

Производство: Бульдозер • Погрузчик

Version	STANDARD
Type	TL
Tyre Size	26.5 - 25

Dimensions US Standard

Usa code	94033331
Ply Rating	28
Overall Width (inch)	27.2
Overall Diameter (inch)	69.9
Static Loaded Radius (inch)	32.1
Rolling Circumference (inch)	206.8
Rim Rec	22.00/3.0
TRA Code	L4

Load capacity (lbs)

mph / psi	69
5	34200

Printed on 24.04.2024 17:41

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..