

## XL GRIP PLUS - Технические спецификации



### Description

Шина XL GRIP PLUS (L-4) разработана специально для эксплуатации на погрузчиках. Благодаря высокому протектору она обладает превосходной стойкостью к порезам и проколам, а также отличается увеличенным сроком службы. Шина XL GRIP PLUS рекомендована для эксплуатации в суровых условиях.

### UM

International Standard

### Construction

 BIAS

### Machinery

Производство: Бульдозер • Погрузчик

Version	STANDARD
Type	TL
Tyre Size	29.5 - 25

## Dimensions International Standard

Ply Rating	36
Overall Width (mm)	760
Overall Diameter (mm)	1915
Static Loaded Radius (mm)	876
Rolling Circumference (mm)	5709
Rim Rec	25.00/3.5
TRA Code	L4
Tread Depth	60

## Load capacity (Kg)

km/h / bar	5.75
10	20890

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 01.06.2025 4:43

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..