

XL GRIP (T) - Технические спецификации



Description

Шины XL GRIP (E-3) лучше всего подходят для большегрузных автомобилей в горнодобывающей промышленности. Специальная резиновая смесь протектора минимизирует повреждения при работе на неровной поверхности. Шины XL GRIP (E-3) отличаются исключительными тяговыми характеристиками и долгим сроком службы.

UM

International Standard

Construction

 BIAS

Machinery

Производство: Дорожный/внедорожный грузовик

Version	STANDARD
Type	TT
Tyre Size	12.00 - 20

Dimensions International Standard

Ply Rating	18
Overall Width (mm)	320
Overall Diameter (mm)	1155
Static Loaded Radius (mm)	545
Rolling Circumference (mm)	3465
Rim Rec	8.5
Rim Alt	8.0

Load capacity (Kg)

km/h / bar	7.20
90 LS/LD	3350

Printed on 10.04.2024 0:59

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..