

XL GRIP ULTRA - Загрузить лист технических данных



Description

XL GRIP ULTRA - это диагональная шина, предназначенная для самосвалов, которые эксплуатируются в тяжелых условиях (например, в шахтах, карьерах и на строительных площадках). Ненаправленный рисунок протектора служит залогом превосходного сцепления в продольном и поперечном направлениях. Шина отличается прочным каркасом с нейлоновыми нитями корда и оптимизированными стяжками, а также специальной резиновой смесью протектора. Все это гарантирует ей невероятную стойкость к порезам и проколам, долгий срок службы, износостойкость и самоочистение даже при работе на каменистых поверхностях.

UM

International Standard

Construction

 BIAS

Machinery

Производство: Дорожный/внедорожный грузовик

SIZE	Version	PR	RIM REC	RIM ALT	OW	OD	SLR	RC	Type
10.00 - 20	STANDARD	18	7.5	7.0	285	1075	505	3257	TT
11.00 - 20	STANDARD	18	8.0	7.5	297	1115	529	3368	TT
12.00 - 20	STANDARD	20	8.5	8.0	320	1155	545	3465	TT
12.00 - 24	INDUSTRIAL	24	8.5	8.0	320	1250	585	3710	TT
12.00 - 24	STANDARD	20	8.5	8.0	320	1250	585	3710	TT

Printed on 28.04.2024 22:46

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..