

## EARTHMAX SR 315 CS - Tekniska specifikationer



### Description

EARTHMAX SR 315 CS L-3S är ett radialdäck helt i stål särskilt konstruerat för lastares framaxlar med kedjor i gruvdrift.

Den speciella däckmönsterkonturen med fasad däcksuldra gör att däckkedjorna sitter bättre längs slitbanan och kring däcksuldran.

Däckets övergripande diameter med kedjor motsvarar diametern för BKT EARTHMAX SR 55 L-5S på bakaxeln, vilket ger hög överensstämmelse mellan fram- och bakdäck.

EARTHMAX SR 315 CS är konstruerat för att minimera risken för skador på framdäcken vid underjordiska grävarbeten med gruvlastmaskiner och lastare.

### UM

US Standard

### Construction

 RADIAL

### Machinery

OTR: Gruvlastmaskin • Hjulastare

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	29.5 R 29
LI/SS	218 A2

## Dimensions US Standard

Usa code	94069378
Overall Width (inch)	30.7
Overall Diameter (inch)	74.4
Static Loaded Radius (inch)	33.1
Rolling Circumference (inch)	225
Rim Rec	25.00/3.5
Rim Alt	24.00/3.5
Star Rating	**
TRA Code	L3S

## Load capacity (lbs)

mph / psi	76	80	83	87	91	94
5	44100	45400	46700	49400	50700	52000

Printed on 4/23/2024 3:30 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..