

EARTHMAX SR 315 CS - Ladda ned faktablad



Description

EARTHMAX SR 315 CS L-3S är ett radialdäck helt i stål särskilt konstruerat för lastares framaxlar med kedjor i gruvdrift.

Den speciella däcktjänsterkonturen med fasad däcksuldra gör att däcktjänsterna sitter bättre längs slitbanan och kring däcksuldran.

Däckets övergripande diameter med kedjor motsvarar diametern för BKT EARTHMAX SR 55 L-5S på bakaxeln, vilket ger hög överensstämmelse mellan fram- och bakdäck.

EARTHMAX SR 315 CS är konstruerat för att minimera risken för skador på framdäcken vid underjordiska grävarbeten med gruvlastmaskiner och lastare.

UM

US Standard

Construction

 RADIAL

Machinery

OTR: Gruvlastmaskin • Hjulastare

SIZE	Version	USACode	TRA Code	Star R	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type
29.5 R 29	CUT RESISTANT COMPOUND	94069378	L3S	**	218 A2	25.00/3.5	24.00/3.5	30.7	74.4	33.1	225	TL
35/65 R 33	CUT RESISTANT COMPOUND	94070992	L3S	***	229 A2	28.00/3.5	-	34.6	76.7	34.1	231.7	TL
35/65 R 33	CUT RESISTANT COMPOUND	94069385	L3S	**	224 A2	28.00/3.5	-	34.6	76.7	34.1	231.7	TL

Printed on 4/22/2024 7:14 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..