

## AGRI GRIP - Tekniska specifikationer



### Description

AGRI GRIP är ett däck för transporter och är speciellt lämpade för sockerrörssläp. AGRI GRIP har ett robust däckhölje som ger hög lastkapacitet och extra stor motståndskraft mot skärande underlag och punkteringar. Dess däckmönster har utformats för längre livslängd.

### UM

International Standard

### Construction

 BIAS

### Machinery

Lantbruk: Släpvagn

Version	DUAL BEAD
Type	TL
Tyre Size	23.1 - 26

## Dimensions International Standard

<b>Ply Rating</b>	18
<b>Overall Width (mm)</b>	595
<b>Overall Diameter (mm)</b>	1560
<b>Static Loaded Radius (mm)</b>	708
<b>Rolling Circumference (mm)</b>	4658
<b>Rim Rec</b>	DW 20 B

## Load capacity (Kg)

<b>km/h / bar</b>	<b>2.60</b>
<b>30 FR LLV</b>	5600

Printed on 4/23/2024 5:56 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..