

AGRIMAX ELOS - Tekniska specifikationer



Description

AGRIMAX ELOS har utmärkt dragkraft även under särskilt svåra förhållanden i blöt terräng, till exempel på risfält och i sumpmarker. Däckets slitbanemönster är utvecklat för att ge optimala självrensande egenskaper, vilket är nödvändigt vid användning på lerig mark och vid förflyttningar. Jordbrukarnas produktivitet har optimerats genom att minska stilleståndstiden. Detta uppnås genom att sidoväggsskydd har integrerats i designen för att ge AGRIMAX ELOS maximalt skydd mot alla typer av skador.

UM

International Standard

Construction

 RADIAL

Machinery

Lantbruk: Traktor

Version	STANDARD
Type	TL
Tyre Size	340/85 R 38 (13.6 R 38)
LI/SS	133 A8/B

Dimensions International Standard

Section Width (mm)	353
Overall Diameter (mm)	1602
Static Loaded Radius (mm)	735
Rolling Circumference (mm)	4774
SRI (mm)	775
Rim Rec	W 12
Rim Alt	W 11
ECE	E4-106R-001477
TRA Code	R2

Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6
50	1135	1320	1505	1690	1875	2060
40	1135	1320	1505	1690	1875	2060
30	1215	1415	1610	1810	2010	2205
10 LT	1525	1770	2020	2270	2520	2765
10 HT	1215	1415	1610	1810	2010	2205

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/11/2025 9:47 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..