

AGRIMAX ELOS - Tekniska specifikationer



Description

AGRIMAX ELOS har utmärkt dragkraft även under särskilt svåra förhållanden i blöt terräng, till exempel på risfält och i sumpmarker. Däckets slitbanemönster är utvecklat för att ge optimala självrensande egenskaper, vilket är nödvändigt vid användning på lerig mark och vid förflyttningar. Jordbrukarnas produktivitet har optimerats genom att minska stilleståndstiden. Detta uppnås genom att sidoväggsskydd har integrerats i designen för att ge AGRIMAX ELOS maximalt skydd mot alla typer av skador.

UM

US Standard

Construction

 RADIAL

Machinery

Lantbruk: Traktor

Version	STANDARD
Type	TL
Tyre Size	340/85 R 38 (13.6 R 38)
LI/SS	133 A8/B

Dimensions US Standard

Usa code	94040452
Section Width (inch)	13.9
Overall Diameter (inch)	63.1
Static Loaded Radius (inch)	28.9
Rolling Circumference (inch)	188
Rim Rec	W 12
Rim Alt	W 11
ECE	E4-106R-001477
TRA Code	R2

Load capacity (lbs)

mph / psi	9	12	15	17	20	23
30	2500	2910	3320	3730	4130	4540
25	2500	2910	3320	3730	4130	4540
20	2680	3120	3550	3990	4430	4860
5 LT	3360	3900	4450	5000	5560	6100
5 HT	2680	3120	3550	3990	4430	4860

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/11/2025 9:56 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..