

AGRIMAX ELOS - Ladda ned faktablad



Description

AGRIMAX ELOS har utmärkt dragkraft även under särskilt svåra förhållanden i blöt terräng, till exempel på risfält och i sumpmarker. Däckets slitbanemönster är utvecklat för att ge optimala självrensande egenskaper, vilket är nödvändigt vid användning på lerig mark och vid förflyttningar. Jordbrukarnas produktivitet har optimerats genom att minska stilleståndstiden. Detta uppnås genom att sidoväggsskydd har integrerats i designen för att ge AGRIMAX ELOS maximalt skydd mot alla typer av skador.

UM

International Standard

Construction

 RADIAL

Machinery

Lantbruk: Traktor

SIZE	Version	TRA Code	LI/SS	RIM REC	RIM ALT	SW	OD	SLR	RC	SRI	Type	ECE
420/85 R 28 (16.9 R 28)	STANDARD	R2	139 A8/B	W 15 L	W 13 ; W 14 L	438	1467	665	4349	700	TL	E4-106R-000768
480/70 R 34	STANDARD	R2	155 A8/155 B	W 15 L	W 16 L ; W 14 L	500	1605	733	4868	750	TL	E11-106R-007532
340/85 R 38 (13.6 R 38)	STANDARD	R2	133 A8/B	W 12	W 11	353	1602	735	4774	775	TL	E4-106R-001477
380/85 R 38 (14.9 R 38)	STANDARD	R2	139 A8/B	W 12	W 11 ; W 13	380	1662	772	4994	775	TL	E4-106R-000779
420/85 R 38 (16.9 R 38)	STANDARD	R2	144 A8/B	W 15 L	W 13 ; W 14 L	438	1735	785	5135	825	TL	E4-106R-000780
480/80 R 38 (18.4 R 38)	STANDARD	R2	149 A8/B	W 16 L	W 15 L ; DW 16 L	489	1803	821	5356	825	TL	E11-106R-002991
710/70 R 38	STANDARD	R2	178 A8/B	DW 23 B	DW 25 B	716	2019	915	6103	925	TL	E11-106R-004896
480/80 R 42 (18.4 R 42)	STANDARD	R2	151 A8/B	DW 16 L	DD 16 L ; W 16 L	489	1890	857	5629	875	TL	E4-106R-001481
520/85 R 42 (20.8 R 42)	STANDARD	R2	157 A8/B	DW 16 L	DD 18 L ; DW 18 L	516	1988	904	5865	925	TL	E4-106R-000793
520/85 R 42 (20.8 R 42)	STANDARD	R2	167A8/B	DW 16 L	DD 18 L ; DW 18 L	516	1988	920	6095	925	TL	E11-106R-0010146
520/85 R 46	STANDARD	R2	169 A8/169 B	DW 16 L	DW 15 L ; DW 18 L ; W 15 L ; W 16 L ; W18 L ; DD 16 L ; DD 18 L	530	2075	957	6293	975	TL	E11-106R-007935

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/11/2025 9:37 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..