

AGRIMAX ELOS - Ladda ned faktablad



Description

AGRIMAX ELOS har utmärkt dragkraft även under särskilt svåra förhållanden i blöt terräng, till exempel på risfält och i sumpmarker. Däckets slitbanemönster är utvecklat för att ge optimala självrensande egenskaper, vilket är nödvändigt vid användning på lerig mark och vid förflyttningar. Jordbrukarnas produktivitet har optimerats genom att minska stilleståndstiden. Detta uppnås genom att sidoväggsskydd har integrerats i designen för att ge AGRIMAX ELOS maximalt skydd mot alla typer av skador.

UM

US Standard

Construction

 RADIAL

Machinery

Lantbruk: Traktor

SIZE	Version	USACode	TRA Code	LI/SS	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
420/85 R 28 (16.9 R 28)	STANDARD	94040810	R2	139 A8/B	W 15 L	W 13 ; W 14 L	17.2	57.8	26.2	171.2	TL	E4-106R-000768
480/70 R 34	STANDARD	94070299	R2	155 A8/155 B	W 15 L	W 16 L ; W 14 L	19.7	63.2	28.9	191.7	TL	E11-106R-0007532
340/85 R 38 (13.6 R 38)	STANDARD	94040452	R2	133 A8/B	W 12	W 11	13.9	63.1	28.9	188	TL	E4-106R-001477
380/85 R 38 (14.9 R 38)	STANDARD	94036134	R2	139 A8/B	W 12	W 11 ; W 13	15	65.4	30.4	196.6	TL	E4-106R-000779
420/85 R 38 (16.9 R 38)	STANDARD	94034512	R2	144 A8/B	W 15 L	W 13 ; W 14 L	17.2	68.3	30.9	202.2	TL	E4-106R-000780
480/80 R 38 (18.4 R 38)	STANDARD	94053766	R2	149 A8/B	W 16 L	W 15 L ; DW 16 L	19.3	71	32.3	210.9	TL	E11-106R-002991
710/70 R 38	STANDARD	94058617	R2	178 A8/B	DW 23 B	DW 25 B	28.2	79.5	36	240.3	TL	E11-106R-004896
480/80 R 42 (18.4 R 42)	STANDARD	94040827	R2	151 A8/B	DW 16 L	DD 16 L ; W 16 L	19.3	74.4	33.7	221.6	TL	E4-106R-001481
520/85 R 42 (20.8 R 42)	STANDARD	94040834	R2	157 A8/B	DW 16 L	DD 18 L ; DW 18 L	20.3	78.3	35.6	230.9	TL	E4-106R-000793
520/85 R 42 (20.8 R 42)	STANDARD	94075850	R2	167A8/B	DW 16 L	DD 18 L ; DW 18 L	20.3	78.3	36.2	240	TL	E11-106R-0010146
520/85 R 46	STANDARD	94070503	R2	169 A8/169 B	DW 16 L	DW 15 L ; DW 18 L ; W 15 L ; W 16 L ; W18 L ; DD 16 L ; DD 18 L	20.9	81.7	37.7	247.8	TL	E11-106R-0007935

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/11/2025 9:41 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..