

AGRIMAX FORTIS - Tekniska specifikationer



Description

AGRIMAX FORTIS är en tillförlitlig partner under alla former av förarbeten, jordbearbetning och transportarbeten. Däcket är avsett att användas med de senaste, modernaste och mest kraftfulla traktorerna och AGRIMAX FORTIS möjliggör mycket stora laster i upp till 65 km/h. Det ger enastående dragförmåga tillsammans med förstklassig hantering och maximal komfort för en perfekt körupplevelse. Däcket är konstruerat med förstärkt däckhölje i nylon för ökad produktivitet på åkern, och marken skonas tack vare minskad jordpackning.

UM

US Standard

Construction

 RADIAL

Machinery

Lantbruk: Besprutningsbil

Version	STANDARD
Type	TL
Tyre Size	600/70 R 30
LI/SS	158 D/161 A8

Dimensions US Standard

Usa code	94032952
Section Width (inch)	24.1
Overall Diameter (inch)	63.1
Static Loaded Radius (inch)	28.5
Rolling Circumference (inch)	189.4
Rim Rec	DW 20 B
Rim Alt	DW 18 L ; W 18 L
ECE	E4-106R-001400
TRA Code	R1W

Load capacity (lbs)

mph / psi	9	12	15	17	20	23	29	35
40	4500	5250	5910	6560	7220	7780	8620	9370
30	4730	5520	6210	6900	7580	8180	9060	9840
25	4890	5710	6430	7140	7860	8470	9380	10200
20	5180	6040	6800	7550	8310	8950	9920	10780
5 LT	6030	7030	7910	8800	9680	10430	11550	12550
5 HT	5180	6040	6800	7550	8310	8950	9920	10780

Printed on 4/13/2024 7:58 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..