

AGRIMAX FORTIS - Tekniska specifikationer



Description

AGRIMAX FORTIS är en tillförlitlig partner under alla former av förarbeten, jordbearbetning och transportarbeten. Däcket är avsett att användas med de senaste, modernaste och mest kraftfulla traktorerna och AGRIMAX FORTIS möjliggör mycket stora laster i upp till 65 km/h. Det ger enastående dragförmåga tillsammans med förstklassig hantering och maximal komfort för en perfekt körupplevelse. Däcket är konstruerat med förstärkt däckhölje i nylon för ökad produktivitet på åkern, och marken skonas tack vare minskad jordpackning.

UM

International Standard

Construction

 RADIAL

Machinery

Lantbruk: Besprutningsbil

| | |
|-----------|-------------|
| Version | SPECIAL |
| Type | TL |
| Tyre Size | 710/75 R 42 |
| LI/SS | 175 D/172 E |

Dimensions International Standard

| | |
|----------------------------|----------------|
| Section Width (mm) | 716 |
| Overall Diameter (mm) | 2133 |
| Static Loaded Radius (mm) | 970 |
| Rolling Circumference (mm) | 6406 |
| SRI (mm) | 1000 |
| Rim Rec | DW 23 B |
| Rim Alt | DW 25 B |
| ECE | E4-106R-001835 |
| TRA Code | R1W |

Load capacity (Kg)

| km/h / bar | 0.6 | 0.8 | 1.0 | 1.2 | 1.4 | 1.6 | 2.0 | 2.4 |
|------------|------|------|------|------|------|------|------|------|
| 70 | 3025 | 3530 | 3970 | 4410 | 4855 | 5230 | 5800 | 6300 |
| 65 | 3315 | 3865 | 4350 | 4830 | 5315 | 5730 | 6350 | 6900 |
| 50 | 3480 | 4060 | 4565 | 5075 | 5580 | 6015 | 6670 | 7245 |
| 40 | 3630 | 4235 | 4765 | 5295 | 5825 | 6275 | 6960 | 7560 |
| 30 | 3810 | 4445 | 5000 | 5555 | 6110 | 6590 | 7305 | 7935 |
| 10 LT | 4440 | 5180 | 5830 | 6475 | 7125 | 7680 | 8510 | 9250 |
| 10 HT | 3810 | 4445 | 5000 | 5555 | 6110 | 6590 | 7305 | 7935 |

Printed on 4/17/2024 5:49 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..