

## AGRIMAX RI 818 - Tekniska specifikationer



### Description

AGRIMAX RI 818 är ett radialdäck utvecklat för användning inom irrigation med bevattningsramper. Det specialdesignade däckmönstret erbjuder utmärkt dragförmåga under våta och leriga förhållanden med enastående självrensande egenskaper.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Lantbruk: Roterande bevattningsmaskin

|           |                            |
|-----------|----------------------------|
| Version   | STANDARD                   |
| Type      | TL                         |
| Tyre Size | 320/85 R 38<br>(12.4 R 38) |
| LI/SS     | 154                        |

## Dimensions International Standard

|                            |            |
|----------------------------|------------|
| Section Width (mm)         | 319        |
| Overall Diameter (mm)      | 1509       |
| Static Loaded Radius (mm)  | 691        |
| Rolling Circumference (mm) | 4565       |
| SRI (mm)                   | 725        |
| Rim Rec                    | W 10       |
| Rim Alt                    | W 9 ; W 11 |

## Load capacity (Kg)

|            |      |
|------------|------|
| km/h / bar | 1.6  |
| CREEP      | 3750 |

\* - CREEP SPEED - 200 FT/30 MIN ( 61 M/30 MIN ) / For CREEP loads inflation pressure to be increased by +6 psi

Printed on 5/9/2024 12:28 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..