

AGRIMAX RI 818 - Ladda ned faktablad



Description

AGRIMAX RI 818 är ett radialdäck utvecklat för användning inom irrigation med bevattningsramper. Det specialdesignade däckmönstret erbjuder utmärkt dragförmåga under våta och leriga förhållanden med enastående självrensande egenskaper.

UM

US Standard

Construction

 RADIAL

Machinery

Lantbruk: Roterande bevattningsmaskin

SIZE	Version	USACode	LI/SS	RIM REC	RIM ALT	SW	OD	SLR	RC	Type
280/85 R 24 (11.2 R 24)	STANDARD	94065578	140	W 10	W 9	11.3	42.8	19.3	128.8	TL
320/85 R 38 (12.4 R 38)	STANDARD	94065585	154	W 10	W 9 ; W 11	12.6	59.4	27.2	179.7	TL

Printed on 5/9/2024 11:21 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..