

AGRIMAX RT 765M - Tekniska specifikationer



Description

AGRIMAX RT 765M är ett däck i BKT 70-serien som passar till banbrytande traktorer och olika tunga användningsområden som jordbearbetning, åker- och vägtransporter, vinskördning och besprutning. Den breda kontaktytan ger bästa möjliga dragförmåga och komfort på alla underlag i alla lägen. Däcket besitter mycket goda självrensande egenskaper och ger minskad jordpackning. Det finns i två storlekar med stålbaltesteknik.

UM

International Standard

Construction

 RADIAL

Machinery

Lantbruk: Besprutningsbil • Traktor • Skördemaskin för vingård

Version	STANDARD
Type	TL
Tyre Size	710/70 R 42
LI/SS	173D/176A8

Dimensions International Standard

Section Width (mm)	716
Overall Diameter (mm)	2061
Static Loaded Radius (mm)	922
Rolling Circumference (mm)	6174
SRI (mm)	975
Rim Rec	DW 23 B
Rim Alt	DW 25 B
ECE	E11-106R-006018
TRA Code	R1W

Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
65	3055	3510	4030	4550	5070	5590	6110	6500
50	3210	3690	4235	4780	5325	5870	6420	6825
40	3350	3845	4415	4985	5555	6125	6695	7120
30	3515	4040	4635	5235	5835	6430	7030	7475
10 LT	4095	4705	5405	6100	6795	7495	8190	8710
10 HT	3515	4040	4635	5235	5835	6430	7030	7475

Printed on 4/19/2024 4:21 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..