

## AGRIMAX RT 765M - Ladda ned faktablad



### Description

AGRIMAX RT 765M är ett däck i BKT 70-serien som passar till banbrytande traktorer och olika tunga användningsområden som jordbearbetning, åker- och vägtransporter, vinskördning och besprutning. Den breda kontaktytan ger bästa möjliga dragförmåga och komfort på alla underlag i alla lägen. Däcket besitter mycket goda självrensande egenskaper och ger minskad jordpackning. Det finns i två storlekar med stålbaltesteknik.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Lantbruk: Besprutningsbil • Traktor • Skördemaskin för vingård

SIZE	Version	TRA Code	LI/SS	RIM REC	RIM ALT	SW	OD	SLR	RC	SRI	Type	ECE
710/70 R 38	SPECIAL	R1W	166 D	DW 23 B	DW 25 B	716	1959	859	5751	925	TL	E11-106R-005837
710/70 R 38	SPECIAL	R1W	175D/178A8	DW 23 B		716	1959	859	5751	925	TL	E11-106R-006000
710/70 R 38	STANDARD	R1W	171D/174A8	DW 23 B		716	1959	859	5751	925	TL	E11-106R-004072
710/70 R 38	STANDARD	R1W	175D/178A8	DW 23 B	DW 25 B	716	1959	859	5751	925	TL	E11-106R-006000
710/70 R 38	STANDARD	R1W	166 D	DW 23 B	DW 25 B	716	1959	859	5751	925	TL	E11-106R-005837
710/70 R 42	SPECIAL	R1W	176 D/179 A8	DW 23 B	DW 25 B	716	2061	922	6174	975	TL	E11-106R-006001
710/70 R 42	SPECIAL	R1W	173D/176A8	DW 23 B	DW 25 B	716	2061	922	6174	975	TL	E11-106R-006018
710/70 R 42	STANDARD	R1W	176D/179A8	DW 23 B	DW 25 B	716	2061	922	6174	975	TL	E11-106R-006001
710/70 R 42	STANDARD	R1W	173D/176A8	DW 23 B	DW 25 B	716	2061	922	6174	975	TL	E11-106R-006018

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 4/29/2025 7:07 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..