

## AGRIMAX RT 765 - Tekniska specifikationer



### Description

AGRIMAX RT 765 är ett däck i BKT 70-serien som passar till banbrytande traktorer och olika tunga användningsområden som jordbearbetning, åker- och vägtransporter, vinskördning och besprutning. Den breda kontaktytan ger bästa möjliga dragförmåga och komfort på alla underlag i alla lägen. Däcket besitter mycket goda självrensande egenskaper och ger minskad jordpackning. Det finns i två storlekar med stålbaltesteknik.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Lantbruk: Besprutningsbil • Traktor • Skördemaskin för vingård

|           |             |
|-----------|-------------|
| Version   | STANDARD    |
| Type      | TL          |
| Tyre Size | 260/70 R 20 |
| LI/SS     | 113 A8/B    |

## Dimensions US Standard

|                              |                |
|------------------------------|----------------|
| Usa code                     | 94030576       |
| Section Width (inch)         | 10.2           |
| Overall Diameter (inch)      | 34.3           |
| Static Loaded Radius (inch)  | 15.8           |
| Rolling Circumference (inch) | 103.9          |
| Rim Rec                      | W 8            |
| Rim Alt                      | 9 ; W 9        |
| ECE                          | E4-106R-000640 |
| TRA Code                     | R1W            |

## Load capacity (lbs)

| mph / psi | 9    | 12   | 15   | 17   | 20   | 23   | 29   | 35   |
|-----------|------|------|------|------|------|------|------|------|
| 30        | 1200 | 1380 | 1580 | 1770 | 1980 | 2180 | 2360 | 2540 |
| 25        | 1200 | 1380 | 1580 | 1770 | 1980 | 2180 | 2360 | 2540 |
| 20        | 1290 | 1480 | 1700 | 1910 | 2130 | 2350 | 2540 | 2720 |
| 5 LT      | 1610 | 1840 | 2120 | 2390 | 2670 | 2930 | 3170 | 3410 |
| 5 HT      | 1290 | 1480 | 1700 | 1910 | 2130 | 2350 | 2540 | 2720 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/1/2025 2:02 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..