

AGRIMAX RT 765 - Tekniska specifikationer



Description

AGRIMAX RT 765 är ett däck i BKT 70-serien som passar till banbrytande traktorer och olika tunga användningsområden som jordbearbetning, åker- och vägtransporter, vinskördning och besprutning. Den breda kontaktytan ger bästa möjliga dragförmåga och komfort på alla underlag i alla lägen. Däcket besitter mycket goda självrensande egenskaper och ger minskad jordpackning. Det finns i två storlekar med stålbaltesteknik.

UM

US Standard

Construction

 RADIAL

Machinery

Lantbruk: Besprutningsbil • Traktor • Skördemaskin för vingård

Version	SPECIAL
Type	TL
Tyre Size	320/70 R 24
LI/SS	116 D

Dimensions US Standard

Usa code	94063154
Section Width (inch)	12.6
Overall Diameter (inch)	43.1
Static Loaded Radius (inch)	19.8
Rolling Circumference (inch)	127.8
Rim Rec	W 10
Rim Alt	W 9 ; W 11
ECE	E11-106R-005827
TRA Code	R1W

Load capacity (lbs)

mph / psi	9	12	15	17	20	23
40	1520	1760	2020	2260	2510	2760
30	1600	1860	2120	2380	2650	2900
25	1660	1940	2220	2480	2760	3020
20	1750	2040	2330	2610	2900	3170
5 LT	2040	2370	2700	3030	3360	3690
5 HT	1750	2040	2330	2610	2900	3170

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/1/2025 1:48 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..