

AGRIMAX RT 765 - Tekniska specifikationer



Description

AGRIMAX RT 765 är ett däck i BKT 70-serien som passar till banbrytande traktorer och olika tunga användningsområden som jordbearbetning, åker- och vägtransporter, vinskördning och besprutning. Den breda kontaktytan ger bästa möjliga dragförmåga och komfort på alla underlag i alla lägen. Däcket besitter mycket goda självrensande egenskaper och ger minskad jordpackning. Det finns i två storlekar med stålbaltesteknik.

UM

US Standard

Construction

 RADIAL

Machinery

Lantbruk: Besprutningsbil • Traktor • Skördemaskin för vingård

Version	SPECIAL
Type	TL
Tyre Size	360/70 R 24
LI/SS	122 D

Dimensions US Standard

Usa code	94063130
TMPH	1
Section Width (inch)	14.1
Overall Diameter (inch)	45.4
Static Loaded Radius (inch)	20.4
Rolling Circumference (inch)	133.7
Rim Rec	W 11
Rim Alt	W 10 ; W 12
ECE	E11-106R-005824
TRA Code	R1W

Load capacity (lbs)

mph / psi	9	12	15	17	20	23
40	1820	2120	2410	2710	3010	3310
30	1920	2230	2540	2850	3160	3470
25	2000	2330	2660	2980	3310	3630
20	2090	2440	2780	3120	3460	3800
5 LT	2450	2840	3240	3640	4030	4430
5 HT	2090	2440	2780	3120	3640	3800

Printed on 4/18/2024 7:46 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..