

## AGRIMAX RT 765 - Tekniska specifikationer



### Description

AGRIMAX RT 765 är ett däck i BKT 70-serien som passar till banbrytande traktorer och olika tunga användningsområden som jordbearbetning, åker- och vägtransporter, vinskördning och besprutning. Den breda kontaktytan ger bästa möjliga dragförmåga och komfort på alla underlag i alla lägen. Däcket besitter mycket goda självrensande egenskaper och ger minskad jordpackning. Det finns i två storlekar med stålbaltesteknik.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Lantbruk: Besprutningsbil • Traktor • Skördemaskin för vingård

Version	SPECIAL
Type	TL
Tyre Size	420/70 R 30
LI/SS	134 D

## Dimensions US Standard

Usa code	94063185
Section Width (inch)	16.5
Overall Diameter (inch)	55
Static Loaded Radius (inch)	24.8
Rolling Circumference (inch)	164.3
Rim Rec	W 13
Rim Alt	W 12 ; W 14 L
ECE	E11-106R-005830
TRA Code	R1W

## Load capacity (lbs)

mph / psi	9	12	15	17	20	23
40	2580	3000	3420	3840	4250	4670
30	2710	3150	3590	4030	4480	4920
25	2820	3280	3750	4210	4670	5130
20	2970	3450	3940	4420	4910	5380
5 LT	3450	4020	4590	5150	5710	6270
5 HT	2970	3450	3940	4420	4910	5380

Printed on 4/19/2024 2:29 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..