AGRIMAX RT 765 - Tekniska specifikationer

Description

AGRIMAX RT 765 är ett däck i BKT 70-serien som passar till banbrytande traktorer och olika tunga användningsområden som jordbearbetning, åker- och vägtransporter, vinskördning och besprutning. Den breda kontaktytan ger bästa möjliga dragförmåga och komfort på alla underlag i alla lägen. Däcket besitter mycket goda självrensande egenskaper och ger minskad jordpackning. Det finns i två storlekar med stålbältesteknik.

UM

US Standard

Construction

RADIAL

Machinery

Lantbruk: Besprutningsbil • Traktor • Skördemaskin för vingård

Version	STANDARD
Type	TL
Tyre Size	480/70 R 28
LI/SS	140 D

Dimensions US Standard

Usa code	94062201
Section Width (inch)	18.9
Overall Diameter (inch)	55.9
Static Loaded Radius (inch)	25
Rolling Circumference (inch)	164.8
Rim Rec	W 15 L
Rim Alt	W 14 L ; W 16 L
ECE	E11-106R-005521
TRA Code	R1W

Load capacity (lbs)

mph / psi	9	12	15	17	20	23
40	3030	3530	4020	4520	5020	5510
30	3190	3700	4230	4750	5270	5790
25	3330	3870	4420	4960	5500	6040
20	3490	4060	4630	5200	5780	6340
5 LT	4070	4730	5400	6060	6720	7390
5 HT	3490	4060	4630	5200	5780	6340

Printed on 4/25/2024 11:08 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..