

AGRIMAX RT 765 - Tekniska specifikationer



Description

AGRIMAX RT 765 är ett däck i BKT 70-serien som passar till banbrytande traktorer och olika tunga användningsområden som jordbearbetning, åker- och vägtransporter, vinskördning och besprutning. Den breda kontaktytan ger bästa möjliga dragförmåga och komfort på alla underlag i alla lägen. Däcket besitter mycket goda självrensande egenskaper och ger minskad jordpackning. Det finns i två storlekar med stålbaltesteknik.

UM

US Standard

Construction

 RADIAL

Machinery

Lantbruk: Besprutningsbil • Traktor • Skördemaskin för vingård

Version	SPECIAL
Type	TL
Tyre Size	520/70 R 34
LI/SS	148 D

Dimensions US Standard

Usa code	94063192
Section Width (inch)	20.3
Overall Diameter (inch)	64.6
Static Loaded Radius (inch)	29.1
Rolling Circumference (inch)	194
Rim Rec	W 16 L
Rim Alt	W 15 L ; W 18 L
ECE	E11-106R-005831
TRA Code	R1W

Load capacity (lbs)

mph / psi	90	12	15	17	20	23
40	3820	4450	5070	5700	6330	6940
30	4020	4670	5330	5990	6920	7300
25	4190	4870	5560	6240	6920	7610
20	4400	5110	5840	6560	7270	7990
5 LT	5130	5960	6800	7640	8480	9310
5 HT	4400	5110	5840	6560	7270	7990

Printed on 4/18/2024 11:27 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..