

## AGRIMAX RT 765 - Tekniska specifikationer



### Description

AGRIMAX RT 765 är ett däck i BKT 70-serien som passar till banbrytande traktorer och olika tunga användningsområden som jordbearbetning, åker- och vägtransporter, vinskördning och besprutning. Den breda kontaktytan ger bästa möjliga dragförmåga och komfort på alla underlag i alla lägen. Däcket besitter mycket goda självrensande egenskaper och ger minskad jordpackning. Det finns i två storlekar med stålbaltesteknik.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Lantbruk: Besprutningsbil • Traktor • Skördemaskin för vingård

Version	STEEL BELTED
Type	TL
Tyre Size	580/70 R 38
LI/SS	180 D

## Dimensions US Standard

Usa code	94038510
Section Width (inch)	22.7
Overall Diameter (inch)	71.9
Static Loaded Radius (inch)	32.3
Rolling Circumference (inch)	216.7
Rim Rec	W 18 L
ECE	E11-106R-005836
TRA Code	R1W

## Load capacity (lbs)

mph / psi	17	23	29	35	41	46	52	58	64	67
40	7010	8540	10870	12080	13230	14260	15280	16250	17170	17640
30	7360	8970	11420	12690	13890	14980	16050	17060	18030	18520
25	7680	9360	11900	13240	14480	15620	16730	17800	18820	19310
20	8070	9830	12500	13900	15210	16410	17570	18690	19750	20280
15	8310	10130	12890	14320	15670	16910	18110	19260	20360	20900

Printed on 4/18/2024 4:28 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..