

## AGRIMAX RT 855 - Tekniska specifikationer



### Description

AGRIMAX RT 855 erbjuder utmärkt dragförmåga och högklassig komfort. Det är huvudsakligen konstruerat för jordbearbetning och transporter på åker och väg, men vissa storlekar lämpar sig även för besprutning och vinskördning. AGRIMAX RT 855 har utmärkta självrensande egenskaper, så att föraren snabbt kan växla mellan åkerarbete och körning på väg.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Lantbruk: Besprutningsbil • Traktor • Skördemaskin för vingård

|           |                            |
|-----------|----------------------------|
| Version   | SPECIAL                    |
| Type      | TL                         |
| Tyre Size | 280/85 R 24<br>(11.2 R 24) |
| LI/SS     | 115 A8/B                   |

## Dimensions US Standard

|                              |                |
|------------------------------|----------------|
| Usa code                     | 94044658       |
| Section Width (inch)         | 11.5           |
| Overall Diameter (inch)      | 42.8           |
| Static Loaded Radius (inch)  | 19.4           |
| Rolling Circumference (inch) | 126.9          |
| Rim Rec                      | W 10           |
| Rim Alt                      | W 9            |
| ECE                          | E4-106R-000611 |
| TRA Code                     | R1W            |

## Load capacity (lbs)

| mph / psi | 9    | 12   | 15   | 17   | 20   | 23   |
|-----------|------|------|------|------|------|------|
| 30        | 1480 | 1720 | 1960 | 2200 | 2450 | 2680 |
| 25        | 1480 | 1720 | 1960 | 2200 | 2450 | 2680 |
| 20        | 1590 | 1850 | 2110 | 2370 | 2620 | 2880 |
| 5 LT      | 1980 | 2300 | 2620 | 2950 | 3270 | 3590 |
| 5 HT      | 1590 | 1850 | 2110 | 2370 | 2620 | 2880 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/1/2025 12:40 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..