

## AGRIMAX RT 855 - Tekniska specifikationer



### Description

AGRIMAX RT 855 erbjuder utmärkt dragförmåga och högklassig komfort. Det är huvudsakligen konstruerat för jordbearbetning och transporter på åker och väg, men vissa storlekar lämpar sig även för besprutning och vinskördning. AGRIMAX RT 855 har utmärkta självrensande egenskaper, så att föraren snabbt kan växla mellan åkerarbete och körning på väg.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Lantbruk: Besprutningsbil • Traktor • Skördemaskin för vingård

Version	SPECIAL
Type	TL
Tyre Size	320/85 R 34 (12.4 R 34)
LI/SS	141 A8/B

## Dimensions International Standard

Section Width (mm)	329
Overall Diameter (mm)	1408
Static Loaded Radius (mm)	645
Rolling Circumference (mm)	4280
SRI (mm)	675
Rim Rec	W 11
Rim Alt	W 9 ; W 10
ECE	E4-106R-000758
TRA Code	R1W

## Load capacity (Kg)

km/h / bar	0.6	0.8	1.2	1.6	2.0	2.4	2.8	3.2	3.6
50	930	1085	1420	1730	1880	2010	2190	2370	2575
40	930	1085	1420	1730	1880	2010	2190	2370	2575
30	995	1160	1520	1850	2015	2155	2350	2540	2760
10 LT	1245	1455	1905	2315	2525	2695	2940	3180	3455
10 HT	995	1160	1520	1850	2015	2155	2350	2540	2760

Printed on 4/27/2024 9:40 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..